


Cetara Vario MKIII Square 6262 36-827/865-3800LM BAP



Technical Details:

Luminous Flux:	3800 lm
LED Output:	36 W
Light Yield:	106 lm/W
Light Color:	dualwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	Funk
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 4014
Number of LED:	240
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	36 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 28-42V, 900mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 55°C

Dimensions:	620x620x10 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	40 (43 room side)
IK Code:	02
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	IP43 raumseits sonst IP40
Cover:	prismatic
Net Weight:	3 g
Type of Packaging:	box
Dimensions of Packaging:	670x670x40
Weight incl. Packaging:	3.5 kg
Content Master Package:	6
Dimensions of Master Package:	715x220x665 mm
Weight Master Package:	18,7 kg
Product Line:	Premio Line
Warranty	3 years
Operating Hours:	35.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557820903
Farbtemperatur: 2700K(warmwhite) - 6500K(kaltwhite)	
mediums Funkfernbedienung veränderbar	
CCT change: from 2700 to 6500 Kelvin with remote	

Information and Downloads:

