


Cetara Office 12431 BAP 36-840-4320LM



Technical Details:

Luminous Flux:	4320 lm
Light Yield:	120 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD
Number of LED:	96
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	36 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
Output of Driver:	DC 32-42V, 900mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	1244x308x10 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (43 room side)
IK Code:	07
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	lacquered
Cover:	prismatic
Net Weight:	2457 g
Type of Packaging:	box
Dimensions of Packaging:	1334x334x36
Weight incl. Packaging:	3.12 kg
Content Master Package:	5
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405 11 90 90
Certifications	CE
Barcode:	4250557822761
LED-Treiber im Lieferumfang enthalten!	
incl. LED driver!	
Low UGR <19 BAP	
PMMA Diffusor	

Information and Downloads:

