


# Cetara 6060-36-840-3900LM IP65



## Technical Details:

Luminous Flux:	3900 lm
LED Output:	31 W
Light Yield:	108 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
LED-Chip:	SMD 4014
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	36 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Output of Driver:	DC 32-42V, 500-900mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-20°C - 55°C

Dimensions:	595x595x12 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	65
IK Code:	02
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Cover:	opal
Net Weight:	3660 g
Type of Packaging:	box
Weight incl. Packaging:	3.82 kg
Content Master Package:	6
Dimensions of Master Package:	650x200x650 mm
Weight Master Package:	23 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557823775
staubdicht und Spritzwasser geschützt IP65	
Achtung EU-Größe nicht für deutsche Decken	
EU size can not be used for German ceilings	

Information and Downloads:

