



Cetara Office 12030 36-830-4100LM



Technical Details:

Luminous Flux:	4100 lm
LED Output:	36 W
Light Yield:	114 lm/W
Light Temperature:	3000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	110 °
Light Emission:	downward
Ignition Time:	<0,5 s
Power Consumption:	36 W
Contains Driver:	✓
Input Driver:	plug connector
Output of Driver:	DC 40V, 900mA
CC/CV:	CC
Input Lamp:	plug connector
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	1195x295x10 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20
IK Code:	02
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	frosted
Net Weight:	2404 g
Type of Packaging:	box
Weight incl. Packaging:	2.7 kg
Content Master Package:	5
Dimensions of Master Package:	1260x330x180 mm
Weight Master Package:	14,47 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557826752
PMMA Diffusor	

Information and Downloads:

