



Fenestra Rectangle Advanced 6030 36-841-3400LM



Technical Details:

Luminous Flux:	3400 lm
LED Output:	40 W
Light Yield:	85 lm/W
Light Temperature:	4100 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	110 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	Samsung
LED-Chip:	SMD 5630
Ignition Time:	<1 s
Power Consumption:	40 W
Contains Driver:	✓
Input Driver:	cable with flying leads
Output of Driver:	DC 30 - 42V, 1050mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	600x300x12 mm
Mounting:	Decke
IP Class:	20
Housing Color	greywhite
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	1800 g
Type of Packaging:	box
Weight incl. Packaging:	2.727 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557805795

Information and Downloads:

