
Technical Data Sheet


Order number: LG59074

LITEGEAR
LED Lighting Solutions

Lucello UP Multi-CCT BL-Aufbau-Panel 6060-40-830/840-5230LM BAP UGR 19







Technical Details:

Luminous Flux:	5230 lm
Light Yield:	140 lm/W
Light Temperature:	3000,3500,4000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Number of LED:	96
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	Power Select (33, 36, 40 W)
Contains Driver:	✓
Driver Manufacturer:	AGT M5 145CC
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
Output of Driver:	DC 25-40V, 850-1050mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>70.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-30°C - 45°C
Storage Temperature:	-30°C - 80°C

Dimensions:	600x600x55 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20 (40 room side)
IK Code:	04
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	steel
Coating:	powder-coated
Special Feature of Housing:	Surface-mounted housing
Cover:	prismatic
Net Weight:	2795 g
Type of Packaging:	box
Weight incl. Packaging:	3.85 kg
Content Master Package:	5
Dimensions of Master Package:	660x475x675 mm
Weight Master Package:	22,18 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	124.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557827117
Bildschirmarbeitsplatz tauglich nach EN 12464-1	
CCT-Select: schaltbare Lichtfarbe 3000, 3500,4000K	
Aufbauleuchte/surface mount panel	

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

OneFitAll, Power Select: 33, 36, 40W