


Lucello Advance Multi-CCT BL-Panel 6060-39-830/850-5460LM BAP UGR 19



Technical Details:

Luminous Flux:	5460 lm
LED Output:	39 W
Light Yield:	140 lm/W
Light Temperature:	3000,4000,5000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD2835
Number of LED:	96
Ignition Time:	<0,5 s
Input Current:	AC 200-264V, 170mA, 50/60Hz
Power Consumption:	Power Select (23-39 W)
Driver Manufacturer:	AGT
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
Output of Driver:	DC 30-38V, 1000mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-30°C - 45°C

Dimensions:	595x595x34 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	40
IK Code:	04
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	steel
Coating:	lacquered
Cover:	prismatic
Net Weight:	1900 g
Type of Packaging:	box
Weight incl. Packaging:	2.3 kg
Content Master Package:	5
Dimensions of Master Package:	635*258*640 mm
Weight Master Package:	12,5 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557825908
Bildschirmarbeitsplatz tauglich nach EN 12464-1	
CCT-Select: schaltbare Lichtfarbe 3000,4000,5000K	
Power Select: 23-39W Treiber einstellbar	
Backlite Technology	

Information and Downloads:

