


Lucello UP Multi-CCT BL-Aufbau-Panel 12030-40-830/840-5230LM BAP UGR 19



Technical Details:

| | |
|------------------------------|-----------------------------|
| Luminous Flux: | 5230 lm |
| Light Yield: | 140 lm/W |
| Light Temperature: | 3000,3500,4000 K |
| Light Color: | CCT Select |
| Color Rendering Index: | ≥80 Ra |
| Color Consistency (SDCM): | <3 |
| Beam Angle: | 90 ° |
| Unified Glare Rating (UGR): | <19 |
| Light Emission: | downward |
| LED-Chip Manufacturer: | San'an |
| LED-Chip: | SMD 2835 |
| Number of LED: | 96 |
| Ignition Time: | <0,5 s |
| Input Current: | AC 220-240V, 50/60Hz |
| Power Consumption: | Power Select (33, 36, 40 W) |
| Contains Driver: | ✓ |
| Driver Manufacturer: | AGT |
| Power Factor (PF): | >0.95 |
| Input Driver: | cable with flying leads |
| Output of Driver: | DC 25-40V, 850, 950, 1050mA |
| CC/CV: | CC |
| Output Current Adjustable: | ✓ |
| Input Lamp: | plug connector |
| Switching Cycles: | >70.000 |
| Electrical Protection Class: | II |
| Ambient Temperature (TA): | -30°C - 45°C |
| Storage Temperature: | -30°C - 80°C |

| | |
|--|-------------------------|
| Dimensions: | 1200x300x55 mm |
| Mounting: | Decke |
| Montageart: | surface mounted |
| IP Class: | 20 (40 room side) |
| IK Code: | 04 |
| Housing Color | white |
| Housing Color (RAL Code): | similar 9016 |
| Housing Material: | steel |
| Coating: | lacquered |
| Special Feature of Housing: | Surface-mounted housing |
| Cover: | prismatic |
| Net Weight: | 3229 g |
| Type of Packaging: | box |
| Weight incl. Packaging: | 4.39 kg |
| Content Master Package: | 5 |
| Dimensions of Master Package: | 1265X475X365 mm |
| Weight Master Package: | 23,95 kg |
| Product Line: | Advance Line |
| Warranty | 5 years |
| Operating Hours: | 124.000 h L80/B10 |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405119090 |
| Certifications | CE |
| Barcode: | 4250557827131 |
| Bildschirmarbeitsplatz tauglich nach EN 12464-1 | |
| CCT-Select: schaltbare Lichtfarbe 3000, 3500,4000K | |
| Aufbauleuchte/surface mount panel | |
| Backlite Technology: 140lm/W max. @3500K 33W | |
| OneFitAll, Power Select 33-40W | |

Information and Downloads:

