


# Quadura PRO Square 62-29-840-4000LM WH



## Technical Details:

|                              |                         |
|------------------------------|-------------------------|
| Luminous Flux:               | 4000 lm                 |
| LED Output:                  | 28 W                    |
| Light Yield:                 | 138 lm/W                |
| Light Temperature:           | 4000 K                  |
| Light Color:                 | neutralwhite            |
| Color Rendering Index:       | ≥80 Ra                  |
| Color Consistency (SDCM):    | <3                      |
| Beam Angle:                  | 95 °                    |
| Unified Glare Rating (UGR):  | <19                     |
| Light Emission:              | downward                |
| LED-Chip Manufacturer:       | Juwei                   |
| LED-Chip:                    | SMD 2835                |
| Ignition Time:               | <0,5 s                  |
| Input Current:               | AC 200 - 240V, 50/60Hz  |
| Power Consumption:           | 29 W                    |
| Contains Driver:             | ✓                       |
| Driver Manufacturer:         | Tridonic                |
| Power Factor (PF):           | >0.98                   |
| Input Driver:                | terminal                |
| CC/CV:                       | CC                      |
| Input Lamp:                  | cable with flying leads |
| Switching Cycles:            | >100.000                |
| Electrical Protection Class: | I                       |
| Ambient Temperature (TA):    | -20°C - 40°C            |
| Storage Temperature:         | -40°C - 60°C            |

|                                                |                       |
|------------------------------------------------|-----------------------|
| Dimensions:                                    | 620x620x26,5 mm       |
| Mounting:                                      | Decke                 |
| Montageart:                                    | recessed              |
| IP Class:                                      | 20                    |
| IK Code:                                       | 06                    |
| Housing Color                                  | white                 |
| Housing Color (RAL Code):                      | similar 9016          |
| Housing Material:                              | steel                 |
| Coating:                                       | powder-coated         |
| Special Feature of Housing:                    | Seilabhängung möglich |
| Cover:                                         | Lens                  |
| Net Weight:                                    | 6040 g                |
| Type of Packaging:                             | box                   |
| Dimensions of Packaging:                       | 715x75x715            |
| Weight incl. Packaging:                        | 6.86 kg               |
| Content Master Package:                        | 1                     |
| Dimensions of Master Package:                  | 715x75x715 mm         |
| Weight Master Package:                         | 6,86 kg               |
| Product Line:                                  | Advance Line          |
| Warranty                                       | 5 years               |
| Operating Hours:                               | 50.000 h L90/B10      |
| Disposal Obligation:                           | ✓                     |
| Customs Tariff Number:                         | 9405499090            |
| Certifications                                 | CE,LM80               |
| Barcode:                                       | 4250557817927         |
| Elegante Rastereinlegeleuchte                  |                       |
| optional auch dimmbare Treiber erhältlich      |                       |
| Mittels Seilset auch abgehängt zu montieren    |                       |
| Optional auch Batterie Notstrommodul lieferbar |                       |

Information and Downloads:

