


Fenestra Value Square MKIII 6060 36-840-4200LM IP66, UGR<21



Technical Details:

Luminous Flux:	4250 lm
LED Output:	34 W
Light Yield:	121 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	110 °
Unified Glare Rating (UGR):	<21
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz
Power Consumption:	35 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.96
Input Driver:	plug connector
Output of Driver:	DC 30 - 40V, 900mA
CC/CV:	CC
Input Lamp:	Power rail
Switching Cycles:	>100.000
Electrical Protection Class:	II
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	595x595x12 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	66
IK Code:	06
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	2924 g
Type of Packaging:	box
Dimensions of Packaging:	625x625x45
Weight incl. Packaging:	3.325 kg
Content Master Package:	4
Dimensions of Master Package:	632 x 695 x180 mm
Weight Master Package:	19,4 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405990090
Certifications	CE,LM80,D
Barcode:	4250557816876
inkl. Klemmdose mit Terminalblock in/out	
Brandschutzklasse UL94-HB	
auch mit dimmbarem Treiber lieferbar	

Information and Downloads:



