



Fenestra Value Square MKIII 6030 36-830-3900LM IP66



Technical Details:

Luminous Flux:	3900 lm
LED Output:	36 W
Light Yield:	108 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥81 Ra
Color Consistency (SDCM):	<5
Beam Angle:	110 °
Unified Glare Rating (UGR):	<20
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz
Power Consumption:	36 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 30 - 42V, 900mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	595x295x12,5 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	66
IK Code:	06
Housing Color	garuwhite
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	1540 g
Type of Packaging:	box
Dimensions of Packaging:	620x320x45
Weight incl. Packaging:	1.8 kg
Content Master Package:	4
Dimensions of Master Package:	632x395x180 mm
Weight Master Package:	9,0 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,ENEC,LM80
Barcode:	4250557811260
inkl. Klemmdose und Terminal für 230V in/out	
incl. junction box and terminal for power in/out	
auch mit dimmbarem Treiber lieferbar	

Information and Downloads:



