


Röhre Performance PRO MKII 1200 18-860-2100LM



Technical Details:

Luminous Flux:	2100 lm
LED Output:	18 W
Light Yield:	117 lm/W
Light Temperature:	6000 K
Light Color:	cold white
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	135 °
LED-Chip Manufacturer:	Epistar
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50Hz
Power Consumption:	18 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Switching Cycles:	>100.000
Ambient Temperature (TA):	-20°C - 50°C

Dimensions:	26x1200 mm
Length of Tube:	1200 mm
Socket:	G13
Rotating Socket:	✓
IP Class:	20
Cover:	opal
Net Weight:	345 g
Type of Packaging:	box
Dimensions of Packaging:	1300x30x30
Weight incl. Packaging:	0.524 kg
Content Master Package:	25
Dimensions of Master Package:	1306x230x180 mm
Weight Master Package:	13,5 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557809724

Information and Downloads:

