

Röhre Performance PRO PT80 1500 35-858-4200LM



Technical Details:

Luminous Flux:	4200 lm
LED Output:	35 W
Light Yield:	120 lm/W
Light Temperature:	5800 K
Light Color:	cold white
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	80 °
LED-Chip Manufacturer:	Samsung
LED-Chip:	SMD 5630
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50Hz
Power Consumption:	35 W
Contains Driver:	✓
Power Factor (PF):	>0.94
Switching Cycles:	>100.000
Ambient Temperature (TA):	-20°C - 50°C

Dimensions:	26x1500 mm
Length of Tube:	1500 mm
Socket:	G13
IP Class:	20
Cover:	clear
Net Weight:	495 g
Type of Packaging:	box
Dimensions of Packaging:	1590Ø35
Weight incl. Packaging:	0.734 kg
Content Master Package:	25
Dimensions of Master Package:	1606x196x210 mm
Weight Master Package:	19,47 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	40.000 h L70/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557806839

Information and Downloads:

