

Integra Medi 9-830-700LM



Technical Details:

Luminous Flux:	700 lm
LED Output:	8 W
Light Yield:	80 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥84 Ra
Color Consistency (SDCM):	<3
Beam Angle:	30 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	Sharp
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz, DC 180-220V
Power Consumption:	9 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 30 - 40V, 220mA
CC/CV:	CC
Input Lamp:	cable with plug
Switching Cycles:	>35.000
Electrical Protection Class:	II
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-20°C - 55°C

Dimensions:	113x58 mm
Cut-Out Dimensions:	100 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	40
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Cover:	Lens
Net Weight:	419 g
Type of Packaging:	box
Dimensions of Packaging:	175x130x113
Weight incl. Packaging:	0.54 kg
Content Master Package:	20
Dimensions of Master Package:	580x360x275 mm
Weight Master Package:	11,8 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557811116

Information and Downloads:

