

Xona Nova MKII 1274 35-840-4600LM Sensor



Technical Details:

Luminous Flux:	4600 lm
LED Output:	34 W
Light Yield:	128 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	288
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz, DC 180-240V
Power Consumption:	36 W
Contains Driver:	✓
Power Factor (PF):	>0.93
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>35.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	1274x140x90 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	09
Housing Color	grey
Housing Material:	Polycarbonat
Special Feature of Housing:	Stainless steel clips
Cover:	frosted
Net Weight:	2761 g
Type of Packaging:	box
Dimensions of Packaging:	1270x145x100
Weight incl. Packaging:	3.207 kg
Content Master Package:	6
Dimensions of Master Package:	1300x325x315 mm
Weight Master Package:	20,27 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557817965
optional mit Notstrombetrieb	
on option with Emergency light function	
Vergleichbare Helligkeit: wie 2 x 36W T8 Röhre	
same brightness as 2 x 36W T8 flourescent tube	

Information and Downloads:



