


# Citana XL 25-CCT-2450LM Triac Dim 244 mm Ø



## Technical Details:

|                              |                           |
|------------------------------|---------------------------|
| Luminous Flux:               | 2450 lm                   |
| LED Output:                  | 25 W                      |
| Light Yield:                 | 98 lm/W                   |
| Light Temperature:           | 3000,4000,6000 K          |
| Light Color:                 | CCT Select                |
| Color Rendering Index:       | ≥80 Ra                    |
| Color Consistency (SDCM):    | <6                        |
| Beam Angle:                  | 110 °                     |
| Light Emission:              | downward                  |
| Dimmable:                    | ✓                         |
| Method of Dimming:           | "Triac Phasen-/abschnitt" |
| LED-Chip:                    | SMD 2835                  |
| Ignition Time:               | <0,5 s                    |
| Power Consumption:           | 25 W                      |
| Contains Driver:             | ✓                         |
| Power Factor (PF):           | >0.9                      |
| CC/CV:                       | CC                        |
| Input Lamp:                  | terminal                  |
| Switching Cycles:            | >30.000                   |
| Electrical Protection Class: | II                        |
| Ambient Temperature (TA):    | -10°C - 40°C              |
| Storage Temperature:         | -10°C - 50°C              |

|                                            |                  |
|--------------------------------------------|------------------|
| Dimensions:                                | 244x85 mm        |
| Cut-Out Dimensions:                        | 195-210 mm       |
| Mounting:                                  | Decke            |
| Montageart:                                | recessed         |
| IP Class:                                  | 20               |
| Housing Color                              | white            |
| Housing Material:                          | Thermoplastic    |
| Special Feature of Housing:                | IP 44 room side  |
| Cover:                                     | frosted          |
| Net Weight:                                | 483 g            |
| Type of Packaging:                         | box              |
| Dimensions of Packaging:                   | 245x245x95       |
| Weight incl. Packaging:                    | 0.651 kg         |
| Content Master Package:                    | 20               |
| Dimensions of Master Package:              | 525x525x510 mm   |
| Weight Master Package:                     | 14,27 kg         |
| Product Line:                              | Essential Line   |
| Warranty                                   | 3 years          |
| Operating Hours:                           | 40.000 h L70/B30 |
| Disposal Obligation:                       | ✓                |
| Customs Tariff Number:                     | 9405499090       |
| Certifications                             | CE               |
| Barcode:                                   | 4250557818429    |
| CCT Select: Farbwahl 3000K, 4000K, 6000K   |                  |
| inkl. Metallring (chrome dunkel)           |                  |
| integrierter Treiber Anschlussklemme       |                  |
| dimmbar mediums Phasen-/ -abschnitt Dimmer |                  |

## Information and Downloads:

