


Lunara ECO MKII 200-740-30000LM



Technical Details:

Luminous Flux:	30000 lm
LED Output:	190 W
Light Yield:	150 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥70 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Light Emission:	
LED-Chip Manufacturer:	Cree
LED-Chip:	SMD 3030
Number of LED:	252
Ignition Time:	<1 s
Power Consumption:	200 W
Contains Driver:	✓
Driver Manufacturer:	Osram
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
Output of Driver:	DC 27-48V
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	500x375x63 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
Pivot Range tilt:	90 °
IP Class:	65
IK Code:	08
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Cover:	Lens
Net Weight:	5490 g
Type of Packaging:	box
Dimensions of Packaging:	560x470x142
Weight incl. Packaging:	7.15 kg
Content Master Package:	1
Weight Master Package:	7,15 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557820088
High System Efficiency:	150 Lumen/Watt
High surge prediction:	6KV/10KV
inkl. 80cm Kabel	
inkl. 80cm cable	

Information and Downloads:



