


# Lunara ECO MKII 30-740-3000LM



## Technical Details:

|                              |                         |
|------------------------------|-------------------------|
| Luminous Flux:               | 3000 lm                 |
| LED Output:                  | 28 W                    |
| Light Yield:                 | 100 lm/W                |
| Light Temperature:           | 4000 K                  |
| Light Color:                 | neutralwhite            |
| Color Rendering Index:       | ≥70 Ra                  |
| Color Consistency (SDCM):    | <3                      |
| Beam Angle:                  | 120 °                   |
| Light Emission:              |                         |
| LED-Chip Manufacturer:       | Lumileds                |
| LED-Chip:                    | SMD 3030                |
| Number of LED:               | 30                      |
| Ignition Time:               | <1 s                    |
| Input Current:               | AC 100 - 277V, 50/60Hz  |
| Power Consumption:           | 30 W                    |
| Contains Driver:             | ✓                       |
| Driver Manufacturer:         | Tureful                 |
| Power Factor (PF):           | >0.9                    |
| Input Driver:                | cable with flying leads |
| CC/CV:                       | CC                      |
| Input Lamp:                  | cable with flying leads |
| Switching Cycles:            | >25.000                 |
| Electrical Protection Class: | I                       |
| Ambient Temperature (TA):    | -20°C - 45°C            |
| Storage Temperature:         | -40°C - 55°C            |

|                                |                     |
|--------------------------------|---------------------|
| Dimensions:                    | 265x165x48 mm       |
| Mounting:                      | ceiling,wall,ground |
| Montageart:                    | surface mounted     |
| Pivot Range tilt:              | 90 °                |
| IP Class:                      | 65                  |
| IK Code:                       | 08                  |
| Housing Color                  | black               |
| Housing Material:              | aluminum            |
| Coating:                       | powder-coated       |
| Cover:                         | clear               |
| Net Weight:                    | 1080 g              |
| Type of Packaging:             | box                 |
| Dimensions of Packaging:       | 265x200x50          |
| Weight incl. Packaging:        | 1.185 kg            |
| Content Master Package:        | 5                   |
| Dimensions of Master Package:  | 280x275x215 mm      |
| Weight Master Package:         | 6,1 kg              |
| Product Line:                  | Essential Line      |
| Warranty                       | 3 years             |
| Operating Hours:               | 30.000 h L80/B20    |
| Disposal Obligation:           | ✓                   |
| Customs Tariff Number:         | 9405421000          |
| Certifications                 | CE,LM80             |
| Barcode:                       | 4250557820057       |
| inkl. 80cm Kabel               |                     |
| incl. 80cm cable               |                     |
| optionale Sensoranschlußbuchse |                     |
| optional sensor connector plug |                     |

## Information and Downloads:



