Technical Data Sheet

Order number: LG59085

RENOVIA 127/36-40-830-4800LM BAP, PMMA

Technical Details:

Luminous Flux:	4800 lm
LED Output:	39 W
Light Yield:	120 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip:	SMD
Number of LED:	80
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	40 W
Contains Driver:	✓
Driver Manufacturer:	AGT
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 32-42V, 850-1050mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-20°C - 50°C

Dimensions:	1270x360x55 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	40
IK Code:	03
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	zweiget. Anbaugehäuse
Cover:	Mikroprismatisch PMMA
Net Weight:	5500 g
Type of Packaging:	box
Weight incl. Packaging:	5.49 kg
Content Master Package:	4
Dimensions of Master Package:	1330x375x420 mm
Weight Master Package:	23,78 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	70.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557823324
Power Select: 36-40W / 850, 950, 1050mA	
PMMA Lightguideplate, anti yellow	
blendfrei: Bildschirmarbeitsplatztauglich	
Flickerfree	

Information and Downloads:

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de