


Integra Mini Downlight 9-830-620LM



Technical Details:

Luminous Flux:	620 lm
LED Output:	8 W
Light Yield:	69 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	90 °
Light Emission:	downward
LED-Chip Manufacturer:	LG
LED-Chip:	SMD 5730
Number of LED:	18
Ignition Time:	<1 s
Input Current:	AC 100-240V, 160mA, 50/60Hz
Power Consumption:	9 W
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 27-42V, 300mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>25.000
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	100x48 mm
Cut-Out Dimensions:	87 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	44
IK Code:	10
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	Low installation depth 48mm
Cover:	frosted
Net Weight:	161 g
Type of Packaging:	box
Dimensions of Packaging:	105x105x105
Weight incl. Packaging:	0.211 kg
Content Master Package:	36
Dimensions of Master Package:	440x335x345 mm
Weight Master Package:	8,41 kg
Product Line:	ECO Line
Warranty	2 years
Operating Hours:	35.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE
Barcode:	4250557805429
IP44 raumseits	

Information and Downloads:



