


Placida Circle 550 45-840-4250LM



Technical Details:

Luminous Flux:	4250 lm
LED Output:	45 W
Light Yield:	94 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Unified Glare Rating (UGR):	<26
Light Emission:	downward
LED-Chip Manufacturer:	Epistar
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200 - 240V, 229mA, 50/60Hz
Power Consumption:	45 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 120V, 365mA
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>30.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	550x18 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	plastic
Cover:	opal
Net Weight:	2242 g
Type of Packaging:	box
Dimensions of Packaging:	560x30x590
Weight incl. Packaging:	2.793 kg
Content Master Package:	5
Dimensions of Master Package:	580x170x625 mm
Weight Master Package:	13,75 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	30.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405114090
Certifications	CE
Barcode:	4250557809625
optional auch mediums Stahlseil-Set pendelbar	

Information and Downloads:



